

The following mounting and splicing accessories have been approved for use with ThermoCable™ Linear Heat Detection wire and are available through SAFE Fire Detection, Inc. The use of non-approved installation accessories may damage the detection wire, cause false alarms and void the warranty.

■ Mounting



TC1027 - Double Loop Cable Tie
Fits 3/4" to 2" sprinkler pipe
Black nylon 6.6 rated from -40° to 185°F

TC1028 - Double Loop Cable Tie
Fits 2 1/2" to 3 1/2" sprinkler pipe
Black nylon 6.6 rated from -40° to 185°F

TC1029 - Double Loop Cable Tie
Fits 4" to 6" sprinkler pipe
Black nylon 6.6 rated from -40° to 185°F



TC1017 - Cable Tie Mount
Use with Single Loop Cable Tie TC1018
Nylon 6.6 cable tie mount - Black
Must use TC1019 Adhesive to adhere to mounting surface



TC1018 - Single Loop Cable Tie
For use with cable tie mount TC1017
Black nylon 6.6 rated from -40° to 185°F



TC1019 - Cable Tie Mount Adhesive
For use with Cable Tie Mount TC1017



TC1012 - Cable Clip
Nylon 6.6 - Black
3/16" mounting hole



TC1013 - Cable Clip
Zinc plated steel cable clip
1/4" mounting hole



TC1014 - Beam Clamp, Spring Steel
Includes nylon 6.6 clip
Designed for material thickness of up to 1/2"



TC1015 - Beam Clamp, Zinc Plated Steel
Includes nylon 6.6 cable clip
Zinc plated steel beam clamp with cable clip
Designed for material thickness up to 7/8"



TC1016 - L-Bracket
Steel bracket for mounting detection cable to equipment



TC1020 - Cable Tray Mounting Clip
Nylon 6.6 spring type cable tray mounting clip for material thickness from 1/16" to 1/4"



TC1021 - 1/16" Cable Tray Mounting Clip Assbly.
Designed for material thickness 1/16" to 5/32"
Includes nylon 6.6 cable clip

TC1022 - 5/32" Cable Tray Mounting Clip Assbly.
Designed for material thickness 5/32" to 1/4"
Includes nylon 6.6 cable clip



TC1023 - 1/8" Universal Mounting Clip Assbly.
Includes nylon 6.6 clip
Designed for material thickness of 1/8" to 1/4"

TC1024 - 5/16" Universal Mounting Clip Assbly.
Includes nylon 6.6 clip
Designed for material thickness of 5/16" to 1/2"



TC100 - Cable Strain Relief Connector
One required for ELR-Box and HDELR-Box
Two required for J-Box and HDJ-Box

■ Splicing



TC1005 - Splicing Block
Two point with screw terminals



TC1007 - Splicing Tape
White
TC1008 - Splicing Tape
Red
TC1009 - Splicing Tape
Blue



TC1010 - Low Temp. Splicing Tape
Black



TC1006 - Sealant Tape
For weatherproof splices



...the leader in early warning air sampling fire technology...

SAFE Fire Detection, Inc.
5915 Stockbridge Drive
Monroe, NC 28110
Phone: 704-821-7920
Fax: 704-821-4327

Satellite Offices in:

- Chicago, Illinois
- Hammond, Indiana
- Houston, Texas
- Los Angeles, California
- Toronto, Canada

E-mail: staff@safefiredetection.com • www.safefiredetection.com