



SAPPHIRE® FIRE SUPPRESSION/DETECTION AND CONTROL SYSTEM VERIFICATION

This form must be completely filled out and mailed or faxed to ANSUL® Quality Services within 10 days of the commissioning of the SAPPHIRE® Fire Suppression and Control System for the SAPPHIRE Environmental Warranty to be in effect. Failure to completely fill out this form and return it within ten days of the system commissioning will invalidate the Environmental Warranty. Refer to the SAPPHIRE Environmental Warranty (Form No. F-2006147) for other information.

Mail To: ANSUL Incorporated
One Stanton Street
Marinette, WI 54143-2542
ATTENTION: Quality Services

Fax To: 1-715-732-3472

Indicate that all of the following items were performed:

- Control Unit and all accessories installed tested/operated for proper performance.
All accessories wired to the AUTOPULSE® Control Unit auxiliary power, supervised circuits, and/or signalling line circuit (SLC) are listed and approved by ANSUL for use with the installed control unit.

Indicate which of the following items was performed (if detector sensitivity can be checked or adjusted):

- Detector sensitivity checked and found to equal value marked on detector.

OR

- Detector sensitivity checked and re-calibrated to equal value marked on detector.

SAPPHIRE Fire Suppression System – Fill in the requested information:

Tank/Cylinder Size Qty. of Tanks/Cylinders Manual Part Number

AUTOPULSE Control System – Indicate which AUTOPULSE Control Unit is installed and fill in the requested information:

Model Part Number Serial Number

Incoming Voltage (Measured) Manual Part Number

Wiring Style – Indicate the wiring style(s) used:

Initiating Circuits Style “B” “D” Indicating Appliance Circuits Style “Y” “Z” SLC Loop Style “4” “6” “7”

Detectors – Indicate quantities of each type installed:

Conventional: Ionization Photoelectric Heat Standard Base Relay Base
Analog Addressable: Ionization Photoelectric Heat Heat/ROR Laser Multi-Sensor
Flame: UV IR UV/IR

Alarms – Indicate quantities of each type installed:

6”/10” Bell Strobe, 15 cd Strobe, 75 cd Horn
Horn/Strobe, 15 cd Horn/Strobe, 75 cd Horn Tone Selected

Other

Releasing Devices – Indicate the type and quantities of each device installed:

Electronic Actuator ANSUL AUTOMAN® II-C

Other Accessories – Indicate type and quantities of each device installed:

Manual Pull Station Abort Switch Pressure Switch
Key-Operated Maintenance Switch Key-Operated Selector Switch Other Switch

CUSTOMER

Location of System
Address Commissioning Date
Scheduled Six Month Maintenance Date
Telephone Hazard System is Protecting
FAX
(signature) (date)

AUTHORIZED ANSUL DISTRIBUTOR

Name Address
(signature) (date)